

# FuelSpec®

## Specialty Fuel Additives

### FuelSpec® 191

#### Sludge Dispersant for Diesel Fuels

All Diesel fuel contains some water. With time, water builds up on the bottom of fuel tanks along with solid material forming sludge. Anaerobic bacteria that live at the water-fuel interface contribute material to this sludge or slime that is difficult to remove. Elimination of water prevents bacteria from living in the tank. Sludge can enter the fuel line and plug filters leading to expensive repairs.

Sludge dispersants contain detergents that disperse water and sludge in fuel tanks into the fuel preventing build up of this material. Sludge dispersants are best used with tanks that have been drained and cleaned prior to use. FuelSpec®191 will:

- Remove water from the tank.
- Prevent corrosion of tank body.
- Eliminate filter plugging in the fuel line.
- Stop abrasion of valves, pumps and injectors by soil in the fuel.
- Stop sludge formation from bacteriological activity.

FuelSpec®191 is specifically designed for use in gasoline and Diesel fuels. The dosage rate for the product is one fluid ounce per ten gallons of fuel. The product is delivered in a pint container with a side reservoir for accurate measurement and dispensing to the fuel tank. The product easily disperses and mixes into the fuel for good results.

FuelSpec® 191 is thoroughly tested and does not violate fuel specifications nor engine warranties when used as instructed. FuelSpec® 191 is registered with the U.S. Environmental Protection Agency (EPA) Registered for on-road use in the United States; EPA Registration No. 235120002.